

# SolarEdge Home Load Controller

SEM-DCS-R08-00



## Optimize energy consumption by controlling appliance usage

- / Controls permanently connected appliances
- / Includes two controlled dry contact switches
- / Switches larger single and three phase loads via an external contactor
- / Wireless connection to the inverter via SolarEdge Home Network
- / Increases savings by maximizing self-consumption through improved utilization of excess PV
- / Optimizes backup operation by switching off non-essential loads
- / Seamlessly integrates into the SolarEdge Home ecosystem
- / Offers a single source for warranty, support, and training, to streamline logistics and operations

# SolarEdge Home Load Controller

SEM-DCS-R08-00

		UNITS
<b>POWER</b>		
AC Input Voltage	90 – 250	Vac
AC Frequency	50 / 60	Hz
Normally Open (NO) Contact Specifications	250Vac up to 8Aac / 30Vdc up to 8Adc	
Normally Closed (NC) Contact Specifications	250Vac up to 4Aac / 30Vdc up to 4Adc	
Relay Switching Cycles	> 20,000	
Operating Hours	50,000	hr
Installation Altitude	2000	m
Power Consumption	< 1.5	W
<b>ENVIRONMENTAL</b>		
Operating Temperature	-10 to +50	°C
Storage Temperature	-20 to +60	°C
Relative Humidity (non-condensing)	0 – 95	%
Ingress Protection	IP30	
<b>DIMENSIONS</b>		
Dimensions L x W x H	100 x 50 x 35 Excluding din-rail adapter	mm
<b>COMMUNICATION</b>		
Supported Communication Protocol	SolarEdge Home Network	
Device Configuration	Monitoring platform/app or SetApp; Ethernet connection is required	
Operating Frequency Range	863 – 870 (EU) 916 – 924 (AUS)	MHz
Modulation	O-QPSK (Quadrature phase shift keying)	
EIRP with Antenna	14 (EU) 20 (AUS)	dBm
<b>TEMPERATURE SENSOR</b>		
Ambient Temperature Sensing Accuracy	±0.5	°C
<b>ACCESSORIES</b>		
Included Mounting Materials	Wood screws, Double-sided tape Rail Mounting: Din-Rail adapter according to IEC/EN 60715	
<b>STANDARD COMPLIANCE</b>		
Applicable Safety Standards	IEC 60730-1:2013+AMD1:2015+AMD2:2020 CSV; UL 916:2021 Ed.5; UL 60730-1:2016 Ed.5; CSA E60730-1:2015 Ed.5	
EMC Standards	IEC/UL/EN 60730-1; EN 301 489-1; EN 301 489-3; EN 61000-3-2; EN 61000-3-3; FCC Part 15, Class B	
Radio Standards	EN 300 220; FCC 15.247C	
Regulation Mark	CE; ETL	

## CONNECTION DIAGRAM

