



FBK_MFW / 108 cells

390W - 410 W

Mono-Crystalline PV Module

URE Peach module uses URE state-of-the-art cell cutting technology, and advanced module manufacturing experiences.



Key Features




Positive power tolerance
+0 ~ +5 watt



100% EL inline inspection
Better module reliability



Withstand heavy loading
front load 5400 Pa & rear load 2400 Pa



Design for 1500 VDC
Reduce the system BOS effectively



Excellent low light performance
3.5% relative eff. Reduction at low
(200W/m²)



PID resistance
Excellent PID resistance performance



Electrical Data

Model - STC		FBK390MFW	FBK395MFW	FBK400MFW	FBK405MFW	FBK410MFW
Maximum Rating Power (Pmax)	[W]	390	395	400	405	410
Module Efficiency	[%]	19.95	20.20	20.46	20.72	20.97
Open Circuit Voltage (Voc)	[V]	36.67	36.91	37.10	37.33	37.58
Maximum Power Voltage	[V]	30.59	30.76	30.98	31.23	31.44
Short Circuit Current (Isc)	[A]	13.63	13.71	13.80	13.87	13.94
Maximum Power Current	[A]	12.75	12.84	12.91	12.97	13.04

*Standard Test Condition (STC): Cell Temperature 25 °C, Irradiance 1000 W/m², AM 1.5

*Values without tolerance are typical numbers.Measurement tolerance: ± 3%

Mechanical Data

Item	Specification
Dimensions	1724 mm (L) ¹ x 1134 mm (W) ¹ x 30 mm (D) ² / 67.87" (L) ¹ x 44.65" (W) ¹ x 1.18" (D) ²
Weight	21.0 kg / 46.30 lbs
Solar Cell	108 pieces monocrystalline solar cells series strings
Front Glass	High transmission glass, 3.2mm thickness
Cell Encapsulation	EVA (Ethylene-Vinyl-Acetate)
Frame	anodized aluminum profile
Junction Box	IP≥ 68, 3 diodes
Cable & Connector	4 mm ² , 300mm in length, compatible with MC4
Package Configuration	36+36 pcs Per Pallet, 936 pcs per 40' HQ container

¹ : With assembly tolerance of ± 2 mm [± 0.08 "]

² : With assembly tolerance of ± 0.8 mm [± 0.03 "]

Operating Conditions

Item	Specification
Mechanical Load	5400 Pa
Maximum System Voltage	1500V
Series Fuse Rating	25 A
Operating Temperature	-40 to 85 °C


Temperature Characteristics

Item	Specification
Nominal Module Operating Temperature	45°C ± 2°C
Temperature Coefficient of Isc	0.046 % / °C
Temperature Coefficient of Voc	-0.266 % / °C
Temperature Coefficient of Pmax	-0.354 % / °C


*Nominal module operating temperature (NMOT): Air mass AM 1.5, irradiance 800W/m², temperature 20°C, windspeed 1 m/s.

*Reduction in efficiency from 1000W/m² to 200W/m² at 25°C: 3.5 ± 2%.


Engineering Drawing (mm)



Dependence on Irradiance



Reliability with Warranty



Output warranty
25
Years

Product Guarantee
12
Years

For more information, please visit us at www.urecorp.com

Taipei Office

9F, NO. 295, Sec. 2, Tiding Blvd.,
Neihu Dist., Taipei 11493, Taiwan

Tel : +886-2-2656-2000

Fax : +886-2-2656-0593

e-mail : sales@urecorp.com

Headquarters

No. 7, Li-Hsin 3rd Road, Hsinchu Science Park
Hsinchu city 30078, Taiwan

Tel : +886-3-578-0011

Fax : +886-3-578-1255