

465 W


MAXIMUM POWER OUTPUT

0/+5 W

POSITIVE POWER TOLERANCE

23.3 %

MAXIMUM EFFICIENCY



Outstanding Visual Appearance

- Designed with aesthetics in mind
- Inheriting Trina Solar awards-winning full black design



Dual-glass Design, High Reliability

- Up to 25 years product warranty and 30 years power warranty
- Excellent fire rating and resistance to harsh environmental conditions
- 5,400 Pa snow load and 4,000 Pa wind load (test loads)



Small in size, bigger on power

- Up to 465 W, 23.3 % module efficiency with high density interconnect technology
- Reduces installation cost with higher power bin and efficiency
- Boost performance in warm weather with low temperature coefficient and operating temperature



Universal solution for residential and C&I rooftops


- Designed for compatibility with existing mainstream inverters, optimizers and mounting systems
- Perfect size and low weight for easy handling. Optimized transportation cost
- Flexible installation solutions for system deployment

Extended Vertex S⁺ Warranty

1 %
1st year max. degradation

0.4 %
Max. annual degradation from year 2 to 30




25 Years
Product Workmanship Warranty



Comprehensive Products and System Certificates



IEC61215/IEC61730/IEC61701/IEC62716
 ISO 9001: Quality Management System
 ISO 14001: Environmental Management System
 ISO14064: Greenhouse Gases Emissions Verification
 ISO45001: Occupational Health and Safety Management System
 ISO14025: Environmental Product Declaration

DIMENSIONS OF PV MODULE (mm)

I-V CURVES OF PV MODULE (450 W)

P-V CURVES OF PV MODULE (450 W)

ELECTRICAL DATA (STC)

	TSM-440 NEG9R.25	TSM-445 NEG9R.25	TSM-450 NEG9R.25	TSM-455 NEG9R.25	TSM-460 NEG9R.25	TSM-465 NEG9R.25
Peak Power Watts- P_{MAX} (Wp)*	440	445	450	455	460	465
Power Tolerance- P_{MAX} (W)**	0/+5					
Maximum Power Voltage- V_{MPP} (V)	44.0	44.3	44.6	45.0	45.4	45.8
Maximum Power Current- I_{MPP} (A)	10.01	10.05	10.09	10.11	10.14	10.16
Open Circuit Voltage- V_{OC} (V)	52.2	52.6	52.9	53.4	53.8	54.2
Short Circuit Current- I_{SC} (A)	10.67	10.71	10.74	10.77	10.81	10.85
Module Efficiency η_m (%)	22.0	22.3	22.5	22.8	23.0	23.3

STC: Irradiance 1000 W/m², Cell Temperature 25 °C, Air Mass AM 1.5. *Measuring tolerance: ±3%. **Power selection up to: +3%

ELECTRICAL DATA (NOCT)

	TSM-440 NEG9R.25	TSM-445 NEG9R.25	TSM-450 NEG9R.25	TSM-455 NEG9R.25	TSM-460 NEG9R.25	TSM-465 NEG9R.25
Maximum Power- P_{MAX} (Wp)	337	341	344	348	352	355
Maximum Power Voltage- V_{MPP} (V)	41.4	41.7	42.0	42.3	42.7	42.8
Maximum Power Current- I_{MPP} (A)	8.14	8.17	8.19	8.22	8.25	8.28
Open Circuit Voltage- V_{OC} (V)	49.5	49.9	50.2	50.6	51.0	51.4
Short Circuit Current- I_{SC} (A)	8.60	8.63	8.66	8.68	8.71	8.74

NOCT: Irradiance at 800 W/m², Ambient Temperature 20 °C, Wind Speed 1 m/s.

MECHANICAL DATA

Solar Cells	Monocrystalline
No. of cells	144 cells
Module Dimensions	1762×1134×30 mm
Weight	21.0 kg
Front Glass	1.6 mm, AR Coated Heat Strengthened Glass
Back Glass	1.6 mm, Heat Strengthened Glass
Frame	30 mm Anodized Aluminium Alloy, Black
J-Box	IP 68, 3 bypass diodes
Cables	Photovoltaic Technology Cable 4.0 mm ² Landscape: 1100/1100 mm Portrait: 200/320 mm*
Connector	TS4 / TS4 Plus / MC4 EV02*

*Special order only

TEMPERATURE RATINGS

NOCT (Nominal Operating Cell Temperature)	43 °C (±2 °C)
Temperature Coefficient of P_{MAX}	-0.29 %/°C
Temperature Coefficient of V_{OC}	-0.24 %/°C
Temperature Coefficient of I_{SC}	0.04 %/°C

MAXIMUM RATINGS

Operational Temperature	-40 to +70 °C
Maximum System Voltage	1500 V DC (IEC)
Max Series Fuse Rating	25 A

WARRANTY

25 year Product Workmanship Warranty
30 year Power Warranty
1 % first year degradation
0.4 % Annual Power Attenuation

(Please refer to product warranty for details)

PACKAGING CONFIGURATION

Modules per box:	36 pieces
Modules per 40' container:	936 pieces